

# MINK MH 0040 A

Hydrogen recirculation blower



**VACUUM SOLUTIONS**

Part of the **BUSCH** GROUP



## **H<sub>2</sub>-approved**

For recirculation of hydrogen in PEM fuel cells

## **Flexible**

Integrated variable speed drive for easy adaptation of volume flow to different process requirements

## **Hermetically tight**

Magnetic coupling for high inlet pressures

# MINK MH 0040 A

Hydrogen recirculation blower




**VACUUM SOLUTIONS**

Part of the **BUSCH** GROUP

Dimensional drawing



Volume flow (at inlet)  
Air at 20°C. Tolerance:  $\pm 10\%$



| MINK MH 0040 A                              |                               |
|---------------------------------------------|-------------------------------|
| Volume flow (at inlet)                      | 40 m³/h                       |
| Pressure (at inlet)                         | 1–3 bar(a)                    |
| Differential pressure                       | max. 0.5 bar                  |
| Leakage rate                                | < 10 Ncm³/h                   |
| Nominal motor rating                        | 1.0 kW                        |
| Nominal motor speed                         | 1200 – 6000 min <sup>-1</sup> |
| Motor current                               | max. 50 A                     |
| Power supply                                | 24 VDC                        |
| Sound pressure level (ISO 2151), KpA = 3 dB | 67 dB(A)                      |
| Weight approx.                              | 11 kg                         |
| Dimensions (L x W x H)                      | 293 x 183 x 150 mm            |
| Gas inlet / outlet                          | G 1" / G 1"                   |

## DO YOU WANT TO KNOW MORE?

Get in touch with us directly!  
[sales@busch.ae](mailto:sales@busch.ae) or +971 6 5528 654



CONTACT FORM



CALL NOW