

PUMA WP 0500 D2

Vacuum boosters



VACUUM SOLUTIONS

Part of the **BUSCH** GROUP



Reliable

Solid lobe design, robust construction made of GGG40 material

High performance

Excellent volumetric efficiency, increases the performance of a vacuum system by up to a factor of ten, specially designed for rough and medium vacuum applications

Flexible

Can be flanged directly on the system at any position, boosts the performance of all types of backing pumps

PUMA WP 0500 D2


Vacuum boosters



VACUUM SOLUTIONS

Part of the **BUSCH** GROUP

Dimensional drawing



Pumping speed

Air at 20°C. Tolerance: $\pm 10\%$

— 50 Hz 60 Hz



PUMA WP 0500 D2	
Nominal pumping speed	520 620 / m³/h (50 / 60 Hz)
Pumping speed	463 / 554 m³/h (50 / 60 Hz)
Max. differential pressure	50 hPa (mbar) (50 / 60 Hz)
Nominal motor rating	2.2 / 3.0 kW (50 / 60 Hz)
Nominal motor speed	3000 / 3600 min ⁻¹ (50 / 60 Hz)
Weight approx.	150 kg
Dimensions (L x W x H)	813 x 345 x 494 mm
Gas inlet / outlet	DN 63 ISO / DN 63 ISO

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!



CONTACT FORM