

# VACTEST TTP 900

Mobile gauge



VACUUM SOLUTIONS



## Intelligent

Measurement range (100 to  $1 \cdot 10^{-3}$  mbar), state-of-the-art microcontroller technology, recording of 2000 measurement points

## Reliable

High industrial standards, robust construction, insensitive against shock venting, robust sensor

## Efficient

Excellent measurement accuracy, up to 100 h operating time, battery and power supply

Accessories, spare parts and options

- Protective case
- 100-240 VAC electrical power supply
- VACTEST Explorer Pro
- USB interface cable for PC
- Calibration certificate

# VACTEST TTP 900

Mobile gauge



VACTEST TTP 900	
Measurement principle	Pirani
Materials exposed to vacuum	Stainless steel 1.4305, tungsten, nickel, glass
Filament material	Tungsten
Measurement range	100-1 · 10 <sup>-3</sup> mbar
Overpressure limit	4 bar abs.
Measurement uncertainty	< 30% of reading (100-20 mbar), < 10% of reading (20-1 · 10 <sup>-2</sup> ), < factor 2 (< 1 · 10 <sup>-2</sup> mbar)
Resolution	1 mbar (100-10 mbar), 2 significant digits (< 10 mbar)
Measuring rate	1-6000 s
Serial interface	USB
Electrical connection	2.5 mm mini-jack for external power supply
Supply voltage	9 V block battery or 15 VDC external
Max. battery operating time	100 h
Power consumption	110 mW
Operating temperature	+5 ... +50 °C
Protection class	IP40
Weight approx.	200 g
Dimensions (L x W x H)	120 x 60 x 25 mm
Vacuum connection	DN 16 ISO-KF

## DO YOU WANT TO KNOW MORE?

Get in touch with us directly!  
[sales@busch.com.au](mailto:sales@busch.com.au) or 1 800 639 087



CONTACT FORM



CALL NOW