

VM 032-150

Mineral Oils



VACUUM SOLUTIONS



Proven performance

Proven mineral oils, for standard industrial applications, for temperatures up to 80 °C

Cost-effective

Proven wear protection, less maintenance costs

Reliable

Optimum lubrication properties, perfectly adapted to Busch vacuum pumps, prevent sealing leakage

VM 032-150

Mineral Oils



VACUUM SOLUTIONS

| | VM 032 | VM 068 | VM 100 | VM 150 |
|-------------------------|------------------------|------------------------|-------------------------|-------------------------|
| Base lubricant | Mineral | Mineral | Mineral | Mineral |
| Viscosity class | ISO VG 32 | ISO VG 68 | ISO VG 100 | ISO VG 150 |
| Kin. viscosity at 40°C | 32 mm ² /s | 68 mm ² /s | 100 mm ² /s | 150 mm ² /s |
| Kin. viscosity at 100°C | 5.2 mm ² /s | 8.5 mm ² /s | 10.7 mm ² /s | 14.5 mm ² /s |
| Density at 15° C | 0.872 kg/l | 0.884 kg/l | 0.880 kg/l | 0.891 kg/l |
| Flash point (COC) | 225 °C | 235 °C | 265 °C | 275 °C |
| Pour point | -18 °C | -15 °C | -12 °C | -12 °C |

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
info@busch.be or +32 (0)9 348 47 22



CONTACT FORM



CALL NOW