

# VACTEST DTP 400 C / DTP 400 DC

Digital transmitter



**VACUUM SOLUTIONS**

Part of the **BUSCH** GROUP



## Intelligent

Measurement range (1000 to  $5 \cdot 10^{-4}$  mbar), state-of-the-art microcontroller technology, fully customizable parameters

## Reliable

High industrial standards, robust construction, optional platinum / rhodium filament for corrosive applications

## Efficient

Modular design, plug and play sensor for maximum uptime

Accessories, spare parts and options

- Replacement sensor
- Active Sensor Controller
- Connecting cable
- RS485 interface converter to Bluetooth
- RS485 interface converter to USB
- Electrical power supply
- Calibration certificate
- VACTEST Explorer Pro

# VACTEST DTP 400 C / DTP 400 DC

Digital transmitter



VACUUM SOLUTIONS

Part of the **BUSCH** GROUP

|                              | VACTEST DTP 400 C                                                                                                          | VACTEST DTP 400 DC                                                                                                         |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Measurement principle        | Pirani                                                                                                                     | Pirani                                                                                                                     |
| Materials exposed to vacuum  | Stainless steel 1.4307, nickel, platinum / rhodium, glass                                                                  | Stainless steel 1.4307, nickel, platinum / rhodium, glass                                                                  |
| Filament material            | Platinum / Rhodium                                                                                                         | Platinum / Rhodium                                                                                                         |
| Measurement range            | 1000–5 · 10 <sup>-4</sup> mbar                                                                                             | 1000–5 · 10 <sup>-4</sup> mbar                                                                                             |
| Overpressure limit           | 10 bar abs.                                                                                                                | 10 bar abs.                                                                                                                |
| Measurement uncertainty      | < 30% of reading (1000–10 mbar), < 10% of reading (10–1 · 10 <sup>-2</sup> mbar), < factor 2 (< 1 · 10 <sup>-2</sup> mbar) | < 30% of reading (1000–10 mbar), < 10% of reading (10–1 · 10 <sup>-2</sup> mbar), < factor 2 (< 1 · 10 <sup>-2</sup> mbar) |
| Repeatability of measurement | ±5% of reading (10–1 · 10 <sup>-2</sup> mbar)                                                                              | ±5% of reading (10–1 · 10 <sup>-2</sup> mbar)                                                                              |
| Leakage rate                 | < 5 · 10 <sup>-10</sup> mbar · l/s                                                                                         | < 5 · 10 <sup>-10</sup> mbar · l/s                                                                                         |
| Reaction time                | < 40 ms                                                                                                                    | < 40 ms                                                                                                                    |
| Serial interface             | RS485                                                                                                                      | RS485                                                                                                                      |
| Electrical connection        | D-Sub, 15 poles, male                                                                                                      | D-Sub, 15 poles, male                                                                                                      |
| Supply voltage               | 20–30 V                                                                                                                    | 20–30 V                                                                                                                    |
| Max. power consumption       | 2.5 W (relays)                                                                                                             | 2.5 / 0.8 W (relays / display)                                                                                             |
| Output signal                | 0–10 V, RS485                                                                                                              | 0–10 V, RS485                                                                                                              |
| Setpoint relay               | 2 dry contacts                                                                                                             | 2 dry contacts                                                                                                             |
| Relay contact rating         | 2A, 50 VAC / 2A, 30 VDC, max. 60 VA                                                                                        | 2A, 50 VAC / 2A, 30 VDC, max. 60 VA                                                                                        |
| Operating temperature        | +5 ... +60 °C                                                                                                              | +5 ... +60 °C                                                                                                              |
| Max. bake-out temperature    | 150 °C                                                                                                                     | 150 °C                                                                                                                     |
| Protection class             | IP40 (IP54 with appropriate D-Sub connector)                                                                               | IP40 (IP54 with appropriate D-Sub connector)                                                                               |
| Weight approx.               | 190 g                                                                                                                      | 190 g                                                                                                                      |
| Dimensions (L x W x H)       | 45 × 66 × 99 mm                                                                                                            | 45 × 66 × 99 mm                                                                                                            |
| Vacuum connection            | DN 16 ISO-KF                                                                                                               | DN 16 ISO-KF                                                                                                               |
| Display                      | Without display                                                                                                            | With display                                                                                                               |

## DO YOU WANT TO KNOW MORE?

Get in touch with us directly!  
[info@busch.ca](mailto:info@busch.ca) or +1 800 363 6360



CONTACT FORM



CALL NOW