

# VSA 032-100

Synthetic Food-Grade Oils



VACUUM SOLUTIONS



## High performance

Synthetic oils based on polyalphaolefin (PAO), outstanding viscosity-temperature stability, excellent cold start characteristics, for pumping speeds up to 100 m<sup>3</sup>/h and operating temperatures up to 100 °C

## Advanced corrosion protection

Advanced anti-corrosion additives for moist product applications, high resistance to water ingress, designed for intermittent use with longer downtimes

## Food-grade

Ideally suited for food applications, H1, Halal and Kosher certification, almost odorless and tasteless

# VSA 032-100

Synthetic Food-Grade Oils



VACUUM SOLUTIONS

	VSA 032	VSA 068	VSA 100
Base lubricant	Polyalphaolefin (PAO)	Polyalphaolefin (PAO)	Polyalphaolefin (PAO)
Viscosity class	ISO VG 32	ISO VG 68	ISO VG 100
Kin. viscosity at 40°C	30.8 mm <sup>2</sup> /s	72.1 mm <sup>2</sup> /s	100.5 mm <sup>2</sup> /s
Kin. viscosity at 100°C	5.9 mm <sup>2</sup> /s	11.3 mm <sup>2</sup> /s	16.2 mm <sup>2</sup> /s
Viscosity index VI	140	149	173
Total acid number	0.66 mg KOH/g	0.56 mg KOH/g	0.66 mg KOH/g
Density at 15.6° C	0.838 kg/l	0.846 kg/l	0.847 kg/l
Flash point (COC)	246 °C	248 °C	260 °C
Pour point	-55 °C	-54 °C	-58 °C
Food certification - H1	InS	InS	InS
Halal certification	HQC	HQC	HQC
Kosher certification	Rabbinat Aachen	Rabbinat Aachen	Rabbinat Aachen

## DO YOU WANT TO KNOW MORE?

Get in touch with us directly!  
[info@busch.ca](mailto:info@busch.ca) or +1 800 363 6360



CONTACT FORM



CALL NOW