

VACTEST TTP 900

Mobile gauge



VACUUM SOLUTIONS



Intelligent

Measurement range (100 to $1 \cdot 10^{-3}$ mbar), state-of-the-art microcontroller technology, recording of 2000 measurement points

Reliable

High industrial standards, robust construction, insensitive against shock venting, robust sensor

Efficient

Excellent measurement accuracy, up to 100 h operating time, battery and power supply

Accessories, spare parts and options

- Protective case
- 100-240 VAC electrical power supply

- VACTEST Explorer Pro
- USB interface cable for PC

- Calibration certificate

VACTEST TTP 900

Mobile gauge



VACUUM SOLUTIONS

VACTEST TTP 900	
Measurement principle	Pirani
Materials exposed to vacuum	Stainless steel 1.4305, tungsten, nickel, glass
Filament material	Tungsten
Measurement range	100–1 · 10 ⁻³ mbar
Overpressure limit	4 bar abs.
Measurement uncertainty	< 30% of reading (100–20 mbar), < 10% of reading (20–1 · 10 ⁻²), < factor 2 (< 1 · 10 ⁻² mbar)
Resolution	1 mbar (100–10 mbar), 2 significant digits (< 10 mbar)
Measuring rate	1–6000 s
Serial interface	USB
Electrical connection	2.5 mm mini-jack for external power supply
Supply voltage	9 V block battery or 15 VDC external
Max. battery operating time	100 h
Power consumption	110 mW
Operating temperature	+5 ... +50 °C
Protection class	IP40
Weight approx.	200 g
Dimensions (L x W x H)	120 × 60 × 25 mm
Vacuum connection	DN 16 ISO-KF

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
info@busch.ca or +1 800 363 6360



CONTACT FORM



CALL NOW