

# VacTest

## Digital Transmitter Pirani DTP 400 C



The Digital Transmitter DTP 400 C is a corrosion resistant Pirani vacuum gauge based on the latest generation of micro-controller architecture. The reliable and robust spiral coil filament provides a wide range of pressure measurement from atmosphere to  $5 \cdot 10^{-4}$  mbar.

- Platinum / Rhodium filament for corrosive applications
- Fully customizable parameters and output signal for easy integration
- Optional display version (DTP 400 DC)
- 0–10 V signal and RS485 interface
- Bake-out up to 150°C without electronics removal
- 2 setpoint relays as standard
- Plug and play sensor replacement



VacTest DTP 400 C

VacTest DTP 400 DC

Technical data		DTP 400 C, DTP 400 DC
Measurement principle		Pirani
Materials exposed to vacuum		Stainless steel 1.4307, nickel, platinum / rhodium, glass
Filament material		Platinum / Rhodium
Measurement range	mbar	1000– $5 \cdot 10^{-4}$
Overpressure limit	bar abs.	10
Measurement uncertainty	% of reading	< 30% (1000–10 mbar)
		< 10% ( $10-1 \cdot 10^{-2}$ mbar)
		< factor 2 ( $< 1 \cdot 10^{-2}$ mbar)
Repeatability of measurement	% of reading	$\pm 5\%$ ( $10-1 \cdot 10^{-2}$ mbar)
Leakage rate	mbar · l/s	$< 5 \cdot 10^{-10}$
Reaction time	ms	< 40
Serial interface		RS485
Electrical connection		D-Sub, 15 poles, male
Supply voltage	V	20–30
Max. power consumption	W	2.5 / 0.8 (relays / display)
Output signal		0–10 V, RS485
Setpoint relay		2 dry contacts
Relay contact rating		2A, 50VAC / 2A, 30VDC, max. 60 VA
Operating temperature	°C	+5 ... +60
Max. bake-out temperature	°C	150
Protection class		IP40 (IP54 with appropriate D-Sub connector)
Approximate weight	g	190
Dimensions (L x W x H)	mm	45 x 66 x 99
Vacuum connection		DN 16 ISO-KF

Vacuum gauges	Part number
DTP 400 C, DN 16 ISO-KF	0656202934
DTP 400 DC, with display, DN 16 ISO-KF	0656202935

Spare parts	Part number
Spare sensor, DN 16 ISO-KF	0680204597

Controllers	Part number
Active Sensor Controller CTR 002, 2 channels	0656202928
Active Sensor Controller CTR 004, 4 channels	0656202929
Power cord	0659930583

Connection	Part number
Connecting cable 2 x D-Sub 15 poles, 2 m	0671204577
Connecting cable 2 x D-Sub 15 poles, 6 m	0671204578
Connecting cable 2 x D-Sub 15 poles, 10 m	0671204580
Connecting cable 2 x D-Sub 15 poles, 20 m	0671204581
RS485 Interface converter to Bluetooth	0680204592
RS485 Interface converter to USB	0671204593
Power supply 100–240 VAC / 50–60Hz, with EU/US/UK/AUS plugs	0671204594

Software	Part number
VacTest explorer, Pro version	0870203191

For the entire product range please refer to the corresponding leaflets.

### Busch LLC

516 Viking Drive | Virginia Beach, VA 23452 | Phone 757-463-7800 | info@buschusa.com | www.buschusa.com

Argentina Australia Austria Bangladesh Belgium Brazil Canada Chile China Colombia Czech Republic Denmark Finland France Germany Hungary India Ireland Israel Italy Japan Korea Malaysia Mexico Netherlands New Zealand Norway Peru Poland Portugal Romania Russia Singapore South Africa Spain Sweden Switzerland Taiwan Thailand Turkey United Arab Emirates United Kingdom USA

Technical data is subject to change. Created in Germany. MG SPAL VACTESTDTP400C USen 06/2018 8BA