

# VACTEST TPP 900

Mobile gauge



## Intelligent

Measurement range (1200 to  $5 \cdot 10^{-4}$  mbar), state-of-the-art microcontroller technology, recording of 2000 measurement points

## Reliable

High industrial standards, robust construction

## Efficient

Excellent measurement accuracy, up to 100 h operating time, battery and power supply

Accessories, spare parts and options

- Protective case
- 100-240 VAC electrical power supply
- VACTEST Explorer Pro
- USB interface cable for PC
- Calibration certificate

# VACTEST TPP 900

Mobile gauge



VACTEST TPP 900	
Measurement principle	Piezoresistive / Pirani
Materials exposed to vacuum	Stainless steel 1.4305, tungsten, nickel, glass
Filament material	Tungsten
Measurement range	1200-5 · 10 <sup>-4</sup> mbar
Overpressure limit	2 bar abs.
Measurement uncertainty	< 0.3% full scale (1200-40 mbar)
Measurement uncertainty	< 10% of reading (40-2 · 10 <sup>-3</sup> mbar), < factor 2 (< 2 · 10 <sup>-3</sup> mbar)
Resolution	1 mbar (1200-1000 mbar), 0.1 mbar (1000-1 mbar), 2 significant digits (< 1 mbar)
Measuring rate	1-6000 s
Serial interface	USB
Electrical connection	2.5 mm mini-jack for external power supply
Supply voltage	9 V block battery or 15 VDC external
Max. battery operating time	100 h
Power consumption	110 mW
Operating temperature	+5 ... +50 °C
Protection class	IP40
Weight approx.	230 g
Dimensions (L x W x H)	120 × 60 × 62.5 mm
Vacuum connection	DN 16 ISO-KF

## DO YOU WANT TO KNOW MORE?

Get in touch with us directly!  
[info@busch.ee](mailto:info@busch.ee) or +372 568 13 203



CONTACT FORM



CALL NOW