## **R5 RA 0600 A ECOTORQUE**

Oil-lubricated rotary vane vacuum pump





Discover all advantages of the product series R5 RA

#### **Efficient**

Up to 50% energy savings thanks to the variable speed drive (VSD), automatic start and stop function with Ecomode

## **High performance**

High pumping speed at low pressure ranges, designed for continuous operation in the rough vacuum range, best-in-class footprint performance ratio

#### **Flexible**

Precise adjustment of vacuum level (pressure control) and pumping speed (speed control) to process requirements, compatible with a wide range of supply voltages

www.buschvacuum.com © Busch Vacuum Solutions 18.05.2024 1/3

# **R5 RA 0600 A ECOTORQUE**

#### Oil-lubricated rotary vane vacuum pump



**Dimensional drawing** 

**Pumping speed** 

Air at 20 °C. Tolerance: ± 10%

The following technical values refer to ISO 50 Hz

|  | R5 RA 0600 A ECOTORQUE       |
|--|------------------------------|
| Nominal pumping speed                        | 330 – 600 m³/h               |
| Ultimate pressure (Gas-ballast valve closed) | 0.1 hPa (mbar)               |
| Ultimate pressure (Gas-ballast valve open)   | 0.5 hPa (mbar)               |
| Ultimate pressure                            | 0.1 hPa (mbar)               |
| Nominal motor rating                         | 18.5 kW                      |
| Nominal motor speed                          | 800 – 1400 min <sup>-1</sup> |
| Ambient temperature                          | 5 40 °C                      |
| Power consumption at 100 mbar                | 6.2 – 10.7 kW                |
| Power consumption at ultimate pressure       | 2.6 – 5.2 kW                 |
| Sound pressure level (ISO 2151)              | 70 – 77 dB(A)                |
| Oil capacity                                 | 11                           |
| Weight approx.                               | 525 kg                       |
| Dimensions (L x W x H)                       | 1322 x 718 x 653 mm          |
| Gas inlet                                    | G 3"                         |

The following technical values refer to ISO 60 Hz

|  | R5 RA 0600 A ECOTORQUE |
|--|------------------------|
| Nominal pumping speed                        | 330 – 600 m³/h         |
| Ultimate pressure (Gas-ballast valve closed) | 0.1 hPa (mbar)         |
| Ultimate pressure (Gas-ballast valve open)   | 0.5 hPa (mbar)         |
| Ultimate pressure                            | 0.1 hPa (mbar)         |
| Nominal motor rating                         | 18.5 kW                |

www.buschvacuum.com © Busch Vacuum Solutions 18.05.2024 2/3

# **R5 RA 0600 A ECOTORQUE**

Oil-lubricated rotary vane vacuum pump



|  | R5 RA 0600 A ECOTORQUE       |
|--|------------------------------|
| Nominal motor speed                    | 800 – 1400 min <sup>-1</sup> |
| Ambient temperature                    | 5 40 °C                      |
| Power consumption at 100 mbar          | 6.2 – 10.7 kW                |
| Power consumption at ultimate pressure | 2.6 – 5.2 kW                 |
| Sound pressure level (ISO 2151)        | 70 – 77 dB(A)                |
| Oil capacity                           | 11                           |
| Weight approx.                         | 525 kg                       |
| Dimensions (L x W x H)                 | 1322 x 718 x 653 mm          |
| Gas inlet                              | G 3"                         |

## DO YOU WANT TO KNOW MORE

Please contact us! info@busch.fi or +358 (0)9 774 60 60







**CALL US NOW** 

www.buschvacuum.com © Busch Vacuum Solutions 18.05.2024 3/3