

# VACTEST TPP 900

Mobile gauge



VACUUM SOLUTIONS



## Intelligent

Measurement range (1200 to  $5 \cdot 10^{-4}$  mbar), state-of-the-art microcontroller technology, recording of 2000 measurement points

## Reliable

High industrial standards, robust construction

## Efficient

Excellent measurement accuracy, up to 100 h operating time, battery and power supply

Accessories, spare parts and options

- Protective case
- 100-240 VAC electrical power supply
- VACTEST Explorer Pro
- USB interface cable for PC
- Calibration certificate

# VACTEST TPP 900

Mobile gauge



| VACTEST TPP 900             |   |
|-----------------------------|---|
| Measurement principle       | Piezoresistive / Pirani   |
| Materials exposed to vacuum | Stainless steel 1.4305, tungsten, nickel, glass   |
| Filament material           | Tungsten  |
| Measurement range           | 1200-5 · 10 <sup>-4</sup> mbar  |
| Overpressure limit          | 2 bar abs.  |
| Measurement uncertainty     | < 0.3% full scale (1200-40 mbar)  |
| Measurement uncertainty     | < 10% of reading (40-2 · 10 <sup>-3</sup> mbar), < factor 2 (< 2 · 10 <sup>-3</sup> mbar) |
| Resolution                  | 1 mbar (1200-1000 mbar), 0.1 mbar (1000-1 mbar), 2 significant digits (< 1 mbar)          |
| Measuring rate              | 1-6000 s  |
| Serial interface            | USB   |
| Electrical connection       | 2.5 mm mini-jack for external power supply  |
| Supply voltage              | 9 V block battery or 15 VDC external  |
| Max. battery operating time | 100 h   |
| Power consumption           | 110 mW  |
| Operating temperature       | +5 ... +50 °C   |
| Protection class            | IP40  |
| Weight approx.              | 230 g   |
| Dimensions (L x W x H)      | 120 × 60 × 62.5 mm  |
| Vacuum connection           | DN 16 ISO-KF  |

## DO YOU WANT TO KNOW MORE?

Get in touch with us directly!  
[busch@buschvacuum.hu](mailto:busch@buschvacuum.hu) or +36 24 887 308



CONTACT FORM



CALL NOW