

VACTEST DTP 400 C / DTP 400 DC

Digital transmitter



Intelligent

Measurement range (1000 to $5 \cdot 10^{-4}$ mbar), state-of-the-art microcontroller technology, fully customizable parameters

Reliable

High industrial standards, robust construction, optional platinum / rhodium filament for corrosive applications

Efficient

Modular design, plug and play sensor for maximum uptime

Accessories, spare parts and options

- Replacement sensor
- Active Sensor Controller
- Connecting cable
- RS485 interface converter to Bluetooth
- RS485 interface converter to USB
- Electrical power supply
- Calibration certificate
- VACTEST Explorer Pro

VACTEST DTP 400 C / DTP 400 DC

Digital transmitter



| | VACTEST DTP 400 C | VACTEST DTP 400 DC |
|------------------------------|--|--|
| Measurement principle | Pirani | Pirani |
| Materials exposed to vacuum | Stainless steel 1.4307, nickel, platinum / rhodium, glass | Stainless steel 1.4307, nickel, platinum / rhodium, glass |
| Filament material | Platinum / Rhodium | Platinum / Rhodium |
| Measurement range | 1000-5 · 10 ⁻⁴ mbar | 1000-5 · 10 ⁻⁴ mbar |
| Overpressure limit | 10 bar abs. | 10 bar abs. |
| Measurement uncertainty | < 30% of reading (1000-10 mbar), < 10% of reading (10-1 · 10 ⁻² mbar), < factor 2 (< 1 · 10 ⁻² mbar) | < 30% of reading (1000-10 mbar), < 10% of reading (10-1 · 10 ⁻² mbar), < factor 2 (< 1 · 10 ⁻² mbar) |
| Repeatability of measurement | ±5% of reading (10-1 · 10 ⁻² mbar) | ±5% of reading (10-1 · 10 ⁻² mbar) |
| Leakage rate | < 5 · 10 ⁻¹⁰ mbar · l/s | < 5 · 10 ⁻¹⁰ mbar · l/s |
| Reaction time | < 40 ms | < 40 ms |
| Serial interface | RS485 | RS485 |
| Electrical connection | D-Sub, 15 poles, male | D-Sub, 15 poles, male |
| Supply voltage | 20-30 V | 20-30 V |
| Max. power consumption | 2.5 W (relays) | 2.5 / 0.8 W (relays / display) |
| Output signal | 0-10 V, RS485 | 0-10 V, RS485 |
| Setpoint relay | 2 dry contacts | 2 dry contacts |
| Relay contact rating | 2A, 50 VAC / 2A, 30 VDC, max. 60 VA | 2A, 50 VAC / 2A, 30 VDC, max. 60 VA |
| Operating temperature | +5 ... +60 °C | +5 ... +60 °C |
| Max. bake-out temperature | 150 °C | 150 °C |
| Protection class | IP40 (IP54 with appropriate D-Sub connector) | IP40 (IP54 with appropriate D-Sub connector) |
| Weight approx. | 190 g | 190 g |
| Dimensions (L x W x H) | 45 × 66 × 99 mm | 45 × 66 × 99 mm |
| Vacuum connection | DN 16 ISO-KF | DN 16 ISO-KF |
| Display | Without display | With display |

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
sales@busch.ie or +353 (0)1 832 13 30



CONTACT FORM



CALL NOW