

DOLPHIN VX 0110-0180 A

Total Recirculation

Liquid ring vacuum pump units



VACUUM SOLUTIONS

Part of the **BUSCH** GROUP



Robust

Compact design, proven technology, reliable operation, minimum maintenance, corrosion-free stainless steel impeller as standard, extremely high vapor and particle tolerance, able to handle entrained liquids, ideal for challenging processes

Low operating cost

Reduced operating costs, cooling water flow minimized, full recirculation and recovery of operating fluid, high efficiency, low sound pressure level, almost vibration free, non-polluting thanks to oil free operation and virtually isothermal compression of gases and vapors

Flexible

Choice of cast iron (EN-GJL-200) or 316 grade stainless steel material housings, cavitation protection included, operating fluids other than water possible, universal motor options, stainless steel separator and support frame ideal for easy cleaning, cooler protected within support frame

DOLPHIN VX 0110-0180 A Total Recirculation


Liquid ring vacuum pump units



VACUUM SOLUTIONS

Part of the **BUSCH** GROUP


Dimensional drawing



Pumping speed

Dry air at 20 °C. Operating fluid water
15°C. Tolerance: - 10%, in accordance
with HEI and Pneurop 6612

— 50 Hz 60 Hz



	DOLPHIN VX 0110 A Total Recirculation	DOLPHIN VX 0140 A Total Recirculation	DOLPHIN VX 0180 A Total Recirculation
Nominal pumping speed	72 / 83 m³/h (50 / 60 Hz)	100 / 120 m³/h (50 / 60 Hz)	122 / 144 m³/h (50 / 60 Hz)
Ultimate pressure	33 hPa (mbar) (50 / 60 Hz)	33 hPa (mbar) (50 / 60 Hz)	33 hPa (mbar) (50 / 60 Hz)
Nominal motor rating	2.2 / 3.0 kW (50 / 60 Hz)	3.0 / 4.0 kW (50 / 60 Hz)	4 / 5.5 kW (50 / 60 Hz)
Weight approx.	159 / 166 kg (50 / 60 Hz)	169 / 175 kg (50 / 60 Hz)	178 / 195 kg (50 / 60 Hz)
Dimensions (L x W x H)	700 x 770 x 825 mm	700 x 770 x 825 mm	700 x 770 x 825 mm
Gas inlet / outlet	G 1½" / R 2"	G 1½" / R 2"	G 1½" / R 2"

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
sales@buschindia.com or +91 (0)124 475 1300



CONTACT FORM



CALL NOW