### DOLPHIN VX 0030/0055 A Total Recirculation



Liquid ring vacuum pump units





Discover all advantages of the product series DOLPHIN VX

#### **Robust**

Compact design, proven technology, reliable operation, minimum maintenance, corrosion-free stainless steel impeller as standard, extremely high vapor and particle tolerance, able to handle entrained liquids, ideal for challenging processes

### Low operating cost

Reduced operating costs, cooling water flow minimized, full recirculation and recovery of operating fluid, high efficiency, low sound pressure level, almost vibration free, non-polluting thanks to oil free operation and virtually isothermal compression of gases and vapors

### **Flexible**

Choice of cast iron (EN-GJL-200) or 316 grade stainless steel material housings, cavitation protection included, operating fluids other than water possible, universal motor options, stainless steel separator and support frame ideal for easy cleaning, cooler protected within support frame

www.buschvacuum.com © Busch Vacuum Solutions 01.07.2025 1/3

# **DOLPHIN VX 0030/0055 A Total Recirculation**



Liquid ring vacuum pump units

#### **Dimensional drawing**

#### **Pumping speed**

Dry air at 20 °C. Operating fluid water 15°C. Tolerance: - 10%, in accordance with HEI and Pneurop 6612

#### The following technical values refer to ISO 50 Hz

	DOLPHIN VX 0030 A Total Recirculation	DOLPHIN VX 0055 A Total Recirculation
Nominal pumping speed	24 m³/h	47 m³/h
Ultimate pressure	33 hPa (mbar)	33 hPa (mbar)
Nominal motor rating	1.1 kW	1.5 kW
Nominal motor speed	1450 min <sup>-1</sup>	1450 min <sup>-1</sup>
Weight approx.	73 kg	83 kg
Dimensions (L x W x H)	540 x 550 x 570 mm	540 x 550 x 570 mm
Gas inlet	G 1"	G 1"
Gas outlet	R 2"	R 2"

www.buschvacuum.com © Busch Vacuum Solutions 01.07.2025 2/3

# **DOLPHIN VX 0030/0055 A Total Recirculation**



Liquid ring vacuum pump units

The following technical values refer to ISO 60 Hz

	DOLPHIN VX 0030 A Total Recirculation	DOLPHIN VX 0055 A Total Recirculation
Nominal pumping speed	31 m³/h	56 m³/h
Ultimate pressure	33 hPa (mbar)	33 hPa (mbar)
Nominal motor rating	1.5 kW	2.2 kW
Nominal motor speed	1750 min-1	1750 min <sup>-1</sup>
Weight approx.	81 kg	91 kg
Dimensions (L x W x H)	540 x 550 x 570 mm	540 x 550 x 570 mm
Gas inlet	G 1"	G 1"
Gas outlet	R 2"	R 2"

Do you want to know more

Please contact us! busch@busch.com.my or +60 (0)3 55 25 95 00







Call us now