

# COBRA NC 0500 B

Dry screw vacuum pump



VACUUM SOLUTIONS



Discover all advantages of the product series COBRA NF

## High performance

Advanced screw design, patented self-balancing screws, specially designed for vacuum packaging

## Efficient

Low cost of ownership, minimal maintenance, long service intervals, high uptime, efficient water cooling

## Easy cleaning

Smooth surface design, can be cleaned using steam jets and conventional detergents

# COBRA NC 0500 B

Dry screw vacuum pump



Dimensional drawing

Pumping speed

Air at 20 °C. Tolerance: ± 10%

The following technical values refer to ISO 50 Hz

COBRA NC 0500 B	
Nominal pumping speed	490 m <sup>3</sup> /h
Ultimate pressure	0.01 hPa (mbar)
Nominal motor rating	9.0 kW
Nominal motor speed	2930 min <sup>-1</sup>
Operating voltage	190–210 / 380–420 V
Sound pressure level (ISO 2151)	69 dB(A)
Weight approx.	460 kg
Dimensions (L x W x H)	1163 x 485 x 557 mm
Gas inlet	G2"
Gas outlet	G1½"

The following technical values refer to ISO 60 Hz

COBRA NC 0500 B	
Nominal pumping speed	490 m <sup>3</sup> /h
Ultimate pressure	0.01 hPa (mbar)
Nominal motor rating	9.0 kW
Nominal motor speed	2930 min <sup>-1</sup>
Operating voltage	190–210 / 380–420 V
Sound pressure level (ISO 2151)	69 dB(A)
Weight approx.	460 kg
Dimensions (L x W x H)	1163 x 485 x 557 mm
Gas inlet	G2"
Gas outlet	G1½"

# COBRA NC 0500 B

Dry screw vacuum pump



VACUUM SOLUTIONS

**DO YOU WANT TO KNOW MORE**

Please contact us!  
sales@busch.co.nz or +64 (0)800 428 724



CONTACT FORM



CALL US NOW