

Genuine Oils VSC 100

Synthetic Oil



VACUUM SOLUTIONS



High performance

Synthetic oil based on Ester, good viscosity-temperature stability for optimum lubrication properties, suitable for high operating temperatures, good chemical tolerance

Efficient

Four times longer durability than comparable mineral oils, good thermal and oxidative stability, extended change intervals, counteracts premature wear, reduces energy consumption

Self-cleaning

Ideally suited for demanding industrial processes, excellent cleaning properties, prevents deposit/lacquer formation caused by abrasion and external process contamination

Genuine Oils VSC 100

Synthetic Oil



Dimensional drawing

The following technical values refer to ISO Hz

VSC 100	
Article number 1 l	0831 168 356
Article number 5 l	0831 168 357
Article number 20 l	0831 210 162
Base lubricant	Ester
Viscosity class	ISO VG 100
Kin. viscosity at 40°C	99.6 mm ² /s
Kin. viscosity at 100°C	9.1 mm ² /s
Viscosity index VI	48
Total acid number	0.09 mg KOH/g
Density at 15° C	0.957 kg/l
Flash point (COC)	250 °C
Pour point	-31 °C
\$(technical_data_compatible_product	COBRA NX 0950 A PLUS PANDA WV 0250 C PANDA WV 0500 C PANDA WV 4500 B PUMA WP 0250 D4 PUMA WP 0500 D2 PUMA WP 0500 D4 PUMA WP 0700 D PUMA WP 1000 D2 PUMA WP 1000 D4 PUMA WP 1250 D2 PUMA WP 2000 D2 PUMA WP 4500 B2 R5 RA 0025 B R5 RA 0025 C/E/F R5 RA 0040 B R5 RA 0040 C/E/F R5 RA 0063 B R5 RA 0063 C/E/F R5 RA 0100 B R5 RA 0100 C/E/F R5 RA 0155 A R5 RA 0160 C R5 RA 0160 D R5 RA 0165 D R5 RA 0202 D R5 RA 0205 D R5 RA 0250 D R5 RA 0255 D R5 RA 0302 D R5 RA 0305 D R5 RA 0400 B R5 RA 0400 C R5 RA 0502 B R5 RA 0502 C R5 RA 0630 B R5 RA 0630 C R5 RA 0760 A PLUS R5 RA 0840 A PLUS R5 RA 1000 A PLUS R5 RA 1000 B R5 RA 1600 A PLUS R5 RA 1600 B R5 RD 0200 A R5 RD 0240 A R5 RD 0300 A R5 RD 0360 A R5 RE 0040 A R5 RE 0040 B R5 RE 0063 A R5 RE 0063 B

DO YOU WANT TO KNOW MORE

Please contact us!
sales@busch.co.nz or +64 (0)800 428 724



CONTACT FORM



CALL US NOW