

# VACTEST DCC 400 / DCC 400 D



## Intelligent

Measurement range ( $2 \cdot 10^{-3}$  mbar to  $5 \cdot 10^{-1}$  mbar), state-of-the-art microcontroller technology, fully customizable parameters

## Reliable

High industrial standards, robust construction, insensitive to contamination and oil vapors

## Efficient

Modular design, plug and play sensor for maximum uptime

### Accessories

- Replacement sensor
- Active Sensor Controller
- Connecting cable
- RS485 interface converter to Bluetooth
- RS485 interface converter to USB
- Electrical power supply
- Calibration certificate
- VACTEST Explorer Pro

# VACTEST DCC 400 / DCC 400 D



## Dimensional drawing

The following technical values refer to ISO Hz

	VACTEST DCC 400 (A)	VACTEST DCC 400 (B)	VACTEST DCC 400 D (A)	VACTEST DCC 400 D (B)
<b>Measurement principle</b>	Inverted magnetron	Inverted magnetron	Inverted magnetron	Inverted magnetron
<b>Materials exposed to vacuum</b>	Stainless steel 1.4307, nickel, tungsten, molybdenum, glass, ceramic	Stainless steel 1.4307, nickel, tungsten, molybdenum, glass, ceramic	Stainless steel 1.4307, nickel, tungsten, molybdenum, glass, ceramic	Stainless steel 1.4307, nickel, tungsten, molybdenum, glass, ceramic
<b>Display</b>	Without display	Without display	With display	With display
<b>Measurement range</b>	$2 \cdot 10^{-3}$ – $5 \cdot 10^{-8}$ mbar	$2 \cdot 10^{-3}$ – $5 \cdot 10^{-8}$ mbar	$2 \cdot 10^{-3}$ – $5 \cdot 10^{-8}$ mbar	$2 \cdot 10^{-3}$ – $5 \cdot 10^{-8}$ mbar
<b>Overpressure limit</b>	10 bar abs.	10 bar abs.	10 bar abs.	10 bar abs.
<b>Measurement uncertainty</b>	< 25% of reading ( $2 \cdot 10^{-3}$ – $1 \cdot 10^{-8}$ mbar)	< 25% of reading ( $2 \cdot 10^{-3}$ – $1 \cdot 10^{-8}$ mbar)	< 25% of reading ( $2 \cdot 10^{-3}$ – $1 \cdot 10^{-8}$ mbar)	< 25% of reading ( $2 \cdot 10^{-3}$ – $1 \cdot 10^{-8}$ mbar)
<b>Repeatability of measurement</b>	±5% of reading ( $2 \cdot 10^{-3}$ – $1 \cdot 10^{-8}$ mbar)	±5% of reading ( $2 \cdot 10^{-3}$ – $1 \cdot 10^{-8}$ mbar)	±5% of reading ( $2 \cdot 10^{-3}$ – $1 \cdot 10^{-8}$ mbar)	±5% of reading ( $2 \cdot 10^{-3}$ – $1 \cdot 10^{-8}$ mbar)
<b>Leakage rate</b>	< $5 \cdot 10^{-10}$ mbar · l/s	< $5 \cdot 10^{-10}$ mbar · l/s	< $5 \cdot 10^{-10}$ mbar · l/s	< $5 \cdot 10^{-10}$ mbar · l/s
<b>Reaction time</b>	< 50 ms	< 50 ms	< 50 ms	< 50 ms
<b>Serial interface</b>	RS485	RS485	RS485	RS485
<b>Electrical connection</b>	D-Sub, 15 poles, male	D-Sub, 15 poles, male	D-Sub, 15 poles, male	D-Sub, 15 poles, male
<b>Supply voltage</b>	20–30 V	20–30 V	20–30 V	20–30 V
<b>Cathode voltage</b>	2.5 kV	2.5 kV	2.5 kV	2.5 kV
<b>Max. power consumption</b>	3 W (relays)	3 W (relays)	3 / 0.8 W (relays / display)	3 / 0.8 W (relays / display)
<b>Output signal</b>	0–10 V, RS485	0–10 V, RS485	0–10 V, RS485	0–10 V, RS485
<b>Setpoint relay</b>	2 dry contacts	2 dry contacts	2 dry contacts	2 dry contacts
<b>Relay contact rating</b>	2A, 50 VAC / 2A, 30 VDC, max. 60 VA	2A, 50 VAC / 2A, 30 VDC, max. 60 VA	2A, 50 VAC / 2A, 30 VDC, max. 60 VA	2A, 50 VAC / 2A, 30 VDC, max. 60 VA
<b>Operating temperature</b>	+5 ... +60 °C	+5 ... +60 °C	+5 ... +60 °C	+5 ... +60 °C
<b>Max. bake-out temperature</b>	160 °C	160 °C	160 °C	160 °C

# VACTEST DCC 400 / DCC 400 D



	VACTEST DCC 400 (A)	VACTEST DCC 400 (B)	VACTEST DCC 400 D (A)	VACTEST DCC 400 D (B)
<b>Protection class</b>	IP40 (IP54 with appropriate D-Sub connector)	IP40 (IP54 with appropriate D-Sub connector)	IP40 (IP54 with appropriate D-Sub connector)	IP40 (IP54 with appropriate D-Sub connector)
<b>Weight approx.</b>	555 g	555 g	555 g	555 g
<b>Dimensions (L x W x H)</b>	45 x 66 x 139 mm	45 x 66 x 139 mm	45 x 66 x 139 mm	45 x 66 x 139 mm
<b>Vacuum connection</b>	DN 25 ISO-KF	DN 40 ISO-KF	DN 25 ISO-KF	DN 40 ISO-KF

**DO YOU WANT TO KNOW MORE**

Please contact us!  
sales@busch.co.nz or +64 (0)800 428 724



CONTACT FORM



CALL US NOW