

VACTEST PPP 700 D



Packageable

Specially designed for direct use in food packaging processes, can be placed inside the packaging and be packaged, robust and compact construction

High performance

Excellent measurement accuracy due to Piezo-Pirani combination sensor, great measurement range (1,200 - 0.01 mbar)

Intuitive operation and handling

Easy control via five buttons, easy-to-read display, integrated li-ion battery, rechargeable via USB-C

VACTEST PPP 700 D



Dimensional drawing

The following technical values refer to ISO Hz

VACTEST PPP 700 D	
Measurement principle	Piezoresistive / Pirani
Display	LCD graphic display, resolution 400 x 240 px
Measurement range	1200–0.01 mbar
Measurement uncertainty () ()	40–0.01 mbar: 10% of reading
Measurement interval	0.02–60 s
Resolution	1200–1 mbar: 0.1 mbar , 0.99–0.01 mbar: 0.01 mbar
Serial interface	USB-C and Bluetooth
Supply voltage	Internal rechargeable lithium-ion battery
Min. battery operating time	48 h
Operating temperature	+5 ... +50 °C
Weight approx.	170 g
Dimensions (L x W x H)	105 x 70 x 25.4 mm
Vacuum connection	Sensor flush mounted in housing, G ## female thread for calibration

DO YOU WANT TO KNOW MORE

Please contact us!
sales@busch.co.nz or +64 (0)800 428 724



CONTACT FORM



CALL US NOW