

# VSE 220

Synthetic Gearbox Oil



VACUUM SOLUTIONS



## High performance

Synthetic oil based on polyalphaolefin (PAO), outstanding viscosity-temperature stability for optimum lubrication even at elevated operating temperatures, excellent cold start characteristics for low temperature applications

## Efficient

Four times longer durability than comparable mineral oils, outstanding thermal and oxidative stability, extended change intervals, counteract premature wear, ensure optimum, long-lasting process performance, reduce energy consumption

## TYR-approved

Perfectly adapted to TYR rotary lobe blowers, effective lubrication and damping for high wear resistance of the gearbox, optimized material compatibility

# VSE 220

Synthetic Gearbox Oil



VACUUM SOLUTIONS

| VSE 220                 |                         |
|-------------------------|-------------------------|
| Base lubricant          | Polyalphaolefin (PAO)   |
| Viscosity class         | ISO VG 220              |
| Kin. viscosity at 40°C  | 220 mm <sup>2</sup> /s  |
| Kin. viscosity at 100°C | 26.1 mm <sup>2</sup> /s |
| Viscosity index VI      | 154                     |
| Density at 15° C        | 0.853 kg/l              |
| Flash point (COC)       | 234 °C                  |
| Pour point              | -48 °C                  |

## DO YOU WANT TO KNOW MORE?

Get in touch with us directly!  
[sales@busch.com.sg](mailto:sales@busch.com.sg) or +65 (0)64 88 08 66



CONTACT FORM



CALL NOW