

VACTEST GRP 100 / GRP 200

Analog transmitter



VACUUM SOLUTIONS

Part of the **BUSCH** GROUP



Flexible

Measurement range (1400 to 1 mbar), flexible analog output signals (4–20 mA or 0–10 V depending on the model)

Reliable

High industrial standards, robust stainless steel case, insensitive against shock venting, protected and robust spiral coil filament, gas type independent

Efficient

Ultra-low leakage rate $< 5 \cdot 10^{-10}$ mbar · l/s

Accessories, spare parts and options

- Active Sensor Controller
- 0-10 V Mating plug
- Hose nozzle – G ¼" male adapter
- 0-10 V Connecting cable
- Calibration certificate

VACTEST GRP 100 / GRP 200

Analog transmitter



VACUUM SOLUTIONS

Part of the **BUSCH GROUP**

	VACTEST GRP 100	VACTEST GRP 200
Measurement principle	Piezoresistive	Piezoresistive
Materials exposed to vacuum	Stainless steel 1.4305, Al ₂ O ₃ ceramic, FKM	Stainless steel 1.4305, Al ₂ O ₃ ceramic, FKM
Measurement range	1400–1 mbar	1400–1 mbar
Overpressure limit	4 bar abs.	4 bar abs.
Measurement uncertainty	< 0.3% full scale	< 0.3% full scale
Leakage rate	< 5 · 10 ⁻¹⁰ mbar · l/s	< 5 · 10 ⁻¹⁰ mbar · l/s
Reaction time	< 20 ms	< 20 ms
Electrical connection	Hirschmann, 6 poles	M12 A, 5 poles
Supply voltage	15–30 V	9–30 V
Max. power consumption	0.6 W	0.6 W
Output signal	0–10 V	4–20 mA
Operating temperature	+5 ... +60 °C	+5 ... +60 °C
Protection class	IP40	IP54
Weight approx.	120 g	120 g
Dimensions (L x W x H)	32 × 32 × 66 mm	32 × 32 × 81 mm
Vacuum connection	DN 16 ISO-KF, G ¼ female thread	DN 16 ISO-KF, G ¼ female thread

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
info@busch.co.th or +66 2 02 66 113



CONTACT FORM



CALL NOW