

VACTEST TRP 900

Mobile gauge



Intelligent

Extended measurement range (1600 to 1 mbar), state-of-the-art microcontroller technology, recording of 2000 measurement points

Reliable

High industrial standards, robust construction, insensitive against shock venting, robust sensor

Efficient

Excellent measurement accuracy, up to 2500 h operating time, battery and power supply

Accessories, spare parts and options

- Protective case
- 100-240 VAC electrical power supply
- VACTEST Explorer Pro
- USB interface cable for PC
- Calibration certificate

VACTEST TRP 900

Mobile gauge



VACTEST TRP 900	
Measurement principle	Piezoresistive
Materials exposed to vacuum	Stainless steel 1.4305, Al ₂ O ₃ ceramic, FKM
Measurement range	1600–1 mbar
Overpressure limit	4 bar abs.
Measurement uncertainty	< 0.3% full scale (linearity, hysteresis, repeatability)
Resolution	1 mbar
Measuring rate	0.05–6000 s
Serial interface	USB
Electrical connection	2.5 mm mini-jack for external power supply
Supply voltage	9 V block battery or 15 VDC external
Max. battery operating time	2500 h
Power consumption	2 mW
Operating temperature	0 ... +50 °C
Protection class	IP40
Weight approx.	200 g
Dimensions (L x W x H)	120 × 60 × 47 mm
Vacuum connection	DN 16 ISO-KF, G ¼ female thread

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
info@busch.co.th or +66 2 02 66 113



CONTACT FORM



CALL NOW