

# COBRA DX 0650/0950 A

Dry screw vacuum pumps



VACUUM SOLUTIONS



Version in illustration with cabinet, standard version comes without cabinet

## Plug&Pump

Easy handling, control panel with touch screen and intuitive user interface, perfectly suited for many industries and applications, including solar power industry, lithium battery production, drying, food packaging, coating, vacuum furnaces and central vacuum systems

## Cost savings

Reduced energy consumption and minimized operating costs, variable speed drive

## Proven technology


Reliable operation thanks to proven dry screw vacuum technology, advanced screw design, minimal maintenance, small footprint

# COBRA DX 0650/0950 A


Dry screw vacuum pumps



Dimensional drawing



Pumping speed  
Air at 20°C. Tolerance: ± 10%



	COBRA DX 0650 A	COBRA DX 0950 A
Nominal pumping speed	max. 650 m <sup>3</sup> /h	max. 950 m <sup>3</sup> /h
Ultimate pressure without gas-ballast valve	0.1 hPa (mbar)	0.01 hPa (mbar)
Nominal motor rating	15 kW	18.5 kW
Nominal motor speed	3000 min <sup>-1</sup> (50 Hz)	4320 min <sup>-1</sup>
Noise level (ISO 2151 at 50 Hz – Standard)	≤ 67 dB(A)	≤ 75 dB(A)
Weight approx.	1125 kg	1125 kg
Dimensions (L x W x H)	1700 x 700 x 1000 mm	1700 x 700 x 1000 mm
Gas inlet / outlet	DN 100 ISO / DN 100 ISO	DN 100 ISO / DN 100 ISO

## DO YOU WANT TO KNOW MORE?

Get in touch with us directly!  
[vakutek@ttmail.com](mailto:vakutek@ttmail.com) or +90 (0)2163100573



CONTACT FORM



CALL NOW