

VM 032-150

Mineral Oils



VACUUM SOLUTIONS



Proven performance

Proven mineral oils, for standard industrial applications, for temperatures up to 80 °C

Cost-effective

Proven wear protection, less maintenance costs

Reliable

Optimum lubrication properties, perfectly adapted to Busch vacuum pumps, prevent sealing leakage

VM 032-150

Mineral Oils



VACUUM SOLUTIONS

	VM 032	VM 068	VM 100	VM 150
Base lubricant	Mineral	Mineral	Mineral	Mineral
Viscosity class	ISO VG 32	ISO VG 68	ISO VG 100	ISO VG 150
Kin. viscosity at 40°C	32 mm ² /s	68 mm ² /s	100 mm ² /s	150 mm ² /s
Kin. viscosity at 100°C	5.2 mm ² /s	8.5 mm ² /s	10.7 mm ² /s	14.5 mm ² /s
Density at 15° C	0.872 kg/l	0.884 kg/l	0.880 kg/l	0.891 kg/l
Flash point (COC)	225 °C	235 °C	265 °C	275 °C
Pour point	-18 °C	-15 °C	-12 °C	-12 °C

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
info@busch.com.tr or +90 216 912 46 04



CONTACT FORM



CALL NOW