


# MINK MB 0018 A

Dry claw vacuum pump



VACUUM SOLUTIONS



## Robust

Specially designed for mobile applications, may be operated under extreme conditions, in temperature ranges between -40 °C and +40 °C and at elevations between -1,000 m and 4,000 m, resistant to severe vibration

## Efficient

Latest claw vacuum technology, dry and contact-free compression, no contamination of pumped medium, intelligent variable speed drive, low energy consumption, long life cycle without servicing

## Compact


Small footprint due to "all-in-one" design

# MINK MB 0018 A

Dry claw vacuum pump




Dimensional drawing



Pumping speed

Air at 20°C. Tolerance:  $\pm 10\%$



MINK MB 0018 A	
Nominal pumping speed	18 m³/h
Ultimate pressure	600 / 450 hPa (mbar)
Nominal motor rating	0.5 kW
Nominal motor speed	6000 min⁻¹
Ambient temperature	-40 ... +40 °C
Sound pressure level (ISO 2151), KpA = 3 dB	73 dB(A)
Weight approx.	6.5 kg
Dimensions (L x W x H)	329.5 x 120 x 199 mm
Gas inlet / outlet	G ¾" / G ½"

## DO YOU WANT TO KNOW MORE?

Get in touch with us directly!  
[info@busch.com.tr](mailto:info@busch.com.tr) or +90 216 912 46 04



CONTACT FORM



CALL NOW