

VSE 220

Synthetic Gearbox Oil



VACUUM SOLUTIONS



High performance

Synthetic oil based on polyalphaolefin (PAO), outstanding viscosity-temperature stability for optimum lubrication even at elevated operating temperatures, excellent cold start characteristics for low temperature applications

Efficient

Four times longer durability than comparable mineral oils, outstanding thermal and oxidative stability, extended change intervals, counteract premature wear, ensure optimum, long-lasting process performance, reduce energy consumption

TYR-approved

Perfectly adapted to TYR rotary lobe blowers, effective lubrication and damping for high wear resistance of the gearbox, optimized material compatibility

VSE 220

Synthetic Gearbox Oil



VACUUM SOLUTIONS

VSE 220	
Base lubricant	Polyalphaolefin (PAO)
Viscosity class	ISO VG 220
Kin. viscosity at 40°C	220 mm ² /s
Kin. viscosity at 100°C	26.1 mm ² /s
Viscosity index VI	154
Density at 15° C	0.853 kg/l
Flash point (COC)	234 °C
Pour point	-48 °C

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
sales@busch.co.uk or +44 (0)1952 67 74 32



CONTACT FORM



CALL NOW