


DOLPHIN VL 0100-0270 A

Total Recirculation

Liquid ring vacuum pump units



VACUUM SOLUTIONS



Robust

Proven technology, reliable operation, corrosion-free stainless steel impeller, extremely high vapor and particle tolerance, choice of cast iron (EN-GJL-200) or 316 grade stainless steel material housings, ATEX-certified version available (Cat. 1 (i/o) IIC, T4)

All-in-One

Unit with base frame, operating fluid separator, heat exchanger, control system, including inlet check valve, fresh liquid supply kit, level indicator with switches, temperature and pressure indicators and cavitation protection

Efficient

Full recirculation of operating fluid, low operating fluid consumption, recovery of condensed vapors and process gases, isolation of cooling liquid from operating fluid, operating fluids other than water possible


DOLPHIN VL 0100-0270 A Total Recirculation

Liquid ring vacuum pump units




VACUUM SOLUTIONS

Dimensional drawing



Dimensional drawing



	DOLPHIN VL 0100 A Total Recirculation	DOLPHIN VL 0180 A Total Recirculation	DOLPHIN VL 0270 A Total Recirculation
Nominal pumping speed	57.7 ACFM	105.9 ACFM	157.1 ACFM
Ultimate pressure	97.5 TORR	97.5 TORR	97.5 TORR
Nominal motor rating	4.0 HP	7.4 HP	10.1 HP
Weight approx.	435.6 / 506 Lbs. (Safe / ATEX)	470.8 / 510.4 Lbs. (Safe / ATEX)	563.2 / 684.2 Lbs. (Safe / ATEX)
Dimensions (L x W x H)	51.6 x 28.6 x 32.2 / 52 x 29 x 37.6 inches (Safe / ATEX)	53.5 x 28.6 x 32.2 / 55.7 x 29 x 37.6 inches (Safe / ATEX)	57.6 x 28.6 x 32.2 / 60.4 x 29 x 37.6 inches (Safe / ATEX)
Gas inlet / outlet	G 1½" / R 2"	G 1½" / R 2"	G 1½" / R 2"

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
info@buschusa.com or +1 757 463 7800



CONTACT FORM



CALL NOW