

R5 KB 0010/0016 E

Oil-lubricated rotary vane vacuum pumps



VACUUM SOLUTIONS

Part of the **BUSCH** GROUP



Compact

Direct-drive construction, reduced height and weight, ideal for installation in vacuum packaging machines

Flexible

Various design options available, easy adaption to individual customer requirements and processes

Reliable

Robust construction, highly durable vanes, proven rotary vane technology, long service life

Accessories, spare parts and options

- Gas-ballast valve
- Filter pressure gauge
- Vacuum pump oils for all applications
- Various inlet filters
- Oil level switch
- Vacuum regulating unit

R5 KB 0010/0016 E


Oil-lubricated rotary vane vacuum pumps



VACUUM SOLUTIONS


Part of the **BUSCH** GROUP

Dimensional drawing



Pumping speed

Air at 70°F. Tolerance: $\pm 10\%$



	R5 KB 0010 E	R5 KB 0016 E
Nominal pumping speed	7.1 ACFM	11.2 ACFM
Ultimate pressure	1.5 Torr	1.5 Torr
Nominal motor rating	0.5 hp	0.7 hp
Nominal motor speed	3600 rpm	3600 rpm
Sound pressure level (ISO 2151), KpA = 3 dB	67 dB(A)	68 dB(A)
Oil capacity	0.3 qts.	0.3 qts.
Weight approx.	35.2 Lbs.	39.6 Lbs.
Dimensions (L x W x H)	10.7 x 8.6 x 7.9 inches	11.9 x 8.5 x 7.9 inches
Gas inlet	G 3/4"	G 3/4"

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!

info@buschusa.com or +1 757 463 7800



CONTACT FORM



CALL NOW