

DOLPHIN VL 0130-0320 A


Total Recirculation

Liquid ring vacuum pump units



VACUUM SOLUTIONS

Part of the **BUSCH** GROUP



All-in-One

Unit with base frame, operating fluid separator, heat exchanger, control system, including inlet check valve, fresh liquid supply kit, level indicator with switches, temperature and pressure indicators and cavitation protection

Efficient

Full recirculation of operating fluid, low operating fluid consumption, recovery of condensed vapors and process gases, isolation of cooling liquid from operating fluid, operating fluids other than water possible

Robust

Proven technology, reliable operation, corrosion-free stainless steel impeller, extremely high vapor and particle tolerance, choice of cast iron (EN-GJL-200) or 316 grade stainless steel material housings, ATEX-certified version available (Cat. 1 (i/o) IIB, T4)

DOLPHIN VL 0130-0320 A

Total Recirculation


Liquid ring vacuum pump units




VACUUM SOLUTIONS

Part of the **BUSCH** GROUP

Dimensional drawing



Dimensional drawing



	DOLPHIN VL 0130 A Total Recirculation	DOLPHIN VL 0170 A Total Recirculation	DOLPHIN VL 0220 A Total Recirculation	DOLPHIN VL 0320 A Total Recirculation
Nominal pumping speed	75.3 ACFM	95.0 ACFM	135.0 ACFM	188.3 ACFM
Ultimate pressure	25 TORR	25 TORR	25 TORR	25 TORR
Nominal motor rating	5.4 hp	7.4 hp	10.1 hp	14.8 hp
Weight approx.	521.4 / 572 Lbs. (Safe / ATEX)	543.4 / 609.4 Lbs. (Safe / ATEX)	642.4 / 728.2 Lbs. (Safe / ATEX)	899.8 / 972.4 Lbs. (Safe / ATEX)
Dimensions (L x W x H)	57.5 x 28.6 x 32.2 / 57.4 x 29 x 37.6 inches (Safe / ATEX)	57.5 x 28.5 x 32.2 / 58.7 x 29 x 37.6 inches (Safe / ATEX)	61.4 x 28.6 x 32.2 / 64.1 x 29 x 37.6 inches (Safe / ATEX)	67.6 x 35.1 x 44.4 / 68.4 x 37.1 x 49.1 inches (Safe / ATEX)
Gas inlet / outlet	G 1½" / R 2"	G 1½" / R 2"	G 1½" / R 2"	G 2" / R 3"

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
info@buschusa.com or +1 757 463 7800



CONTACT FORM



CALL NOW