

COBRA DX 0650/0950 A

Dry screw vacuum pumps



VACUUM SOLUTIONS



Plug&Pump

Easy handling, control panel with touch screen and intuitive user interface, perfectly suited for many industries and applications, including solar power industry, lithium battery production, drying, food packaging, coating, vacuum furnaces and central vacuum systems

Cost savings

Reduced energy consumption and minimized operating costs, variable speed drive

Proven technology

Reliable operation thanks to proven dry screw vacuum technology, advanced screw design, minimal maintenance, small footprint

Accessories, spare parts and options

- Air-cooled version available


COBRA DX 0650/0950 A

Dry screw vacuum pumps




VACUUM SOLUTIONS

Dimensional drawing



Pumping speed

Air at 70°F. Tolerance: ± 10%



	COBRA DX 0650 A	COBRA DX 0950 A
Nominal pumping speed	382.5 ACFM	559.1 ACFM
Ultimate pressure without gas-ballast valve	0.075 TORR	0.075 TORR
Nominal motor rating	20 HP	25 HP
Nominal motor speed	3000 RPM	4320 RPM
Noise level (ISO 2151 at 50 Hz - Standard)	≤ 67 dB(A)	≤ 75 dB(A)
Weight approx.	2475 Lbs.	2475 Lbs.
Dimensions (L x W x H)	66.9 x 27.6 39.4 x inches	66.9 x 27.6 39.4 x inches
Gas inlet / outlet	DN 100 ISO / DN 100 ISO	DN 100 ISO / DN 100 ISO

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
info@buschusa.com or +1 757 463 7800



CONTACT FORM



CALL NOW