

DOLPHIN VX 0030/0055 A

Partial Recirculation

Liquid ring vacuum pump units



Robust

Compact design, proven technology, reliable operation, minimum maintenance, corrosion-free stainless steel impeller as standard, extremely high vapor and particle tolerance, able to handle entrained liquids, ideal for challenging processes

Low operating cost

Reduced utility costs, up to 85% fresh water savings using simple thermostatic control valve, high efficiency, low sound pressure level, almost vibration free, non-polluting thanks to oil-free operation and virtually isothermal compression of gases and vapors

Flexible

Choice of cast iron (EN-GJL-200) or 316 grade stainless steel material housings, cavitation protection included, operating fluids other than water possible, universal motor options, stainless steel separator and support frame ideal for easy cleaning


DOLPHIN VX 0030/0055 A

Partial Recirculation

Liquid ring vacuum pump units




Dimensional drawing



Pumping speed

Dry air at 70°F. Operating fluid water 59°F Tolerance: - 10% in accordance with HEI and Pneurop 6612



DOLPHIN VX 0030 A Partial Recirculation		DOLPHIN VX 0055 A Partial Recirculation	
Nominal pumping speed	18 ACFM	33 ACFM	
Ultimate pressure	25 TORR	25 TORR	
Nominal motor rating	2.0 HP	3.0 HP	
Weight approx.	183 Lbs.	205 Lbs.	
Dimensions (L x W x H)	21.3 x 21.7 x 22.4 inches	21.3 x 21.7 x 22.4 inches	
Gas inlet / outlet	G1" / R2"	G1" / R2"	

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!
info@buschusa.com or +1 757 463 7800



CONTACT FORM



CALL NOW