

R5 RA 0840 A ECOTORQUE

Oil-Lubricated Rotary Vane Vacuum Pumps



VACUUM SOLUTIONS



Efficient

Up to 50% energy savings thanks to the variable speed drive (ECOTORQUE), Ecomode with automatic start and stop function

Flexible

Precise adjustment of vacuum level (pressure control) and pumping speed (speed control) to process requirements, compatible with a wide range of supply voltages, easy control and monitoring of up to eight vacuum pumps with optional ECOTORQUE Master Control

High performance

High pumping speed at low pressure ranges, designed for continuous operation in the rough vacuum range, best-in-class footprint performance ratio

Accessories, spare parts and options


- Single or double gas-ballast valve, manual or solenoid operation
- Various inlet filters
- Various temperature and pressure gauges
- Energy recuperation kit with water/oil heat exchanger
- Vacuum pump oils for all applications

R5 RA 0840 A ECOTORQUE

Oil-Lubricated Rotary Vane Vacuum Pumps



Dimensional drawing



Pumping speed

Air at 70°F. Tolerance: $\pm 10\%$

___ Min. speed Max. speed



R5 RA 0840 A ECOTORQUE	
Nominal pumping speed	230 – 494 ACFM
Ultimate pressure (Gas-ballast valve closed)	0.075 TORR
Nominal motor speed	700 – 1400 RPM
Power consumption at ultimate pressure	5.9 – 12.4 HP
Sound pressure level (ISO 2151), KpA = 3 dB	80 dB(A)
Oil capacity	16 qts.
Weight approx.	1279 Lbs.
Dimensions (L x W x H)	66.1 x 34.1 x 28.5 inches
Gas inlet	G 3"

*Gas outlet G 3" optional

DO YOU WANT TO KNOW MORE?

Get in touch with us directly!

info@buschusa.com or +1 757 463 7800



CONTACT FORM



CALL NOW