

# COMBI CMM

Vacuum pump unit



## Efficient

Latest dry claw vacuum technology, substantial energy savings compared to conventional vacuum generators, cost-effective

## Nearly maintenance-free

Dry and contact-free operation, solution based on MINK MM dry claw vacuum pumps

## Flexible

Easy adaption to individual customer requirements and processes

# COMBI CMM

Vacuum pump unit



VACUUM SOLUTIONS

### Dimensional drawing

### Pumping speed

Air at 20 °C. Tolerance: ± 10%

The following technical values refer to ISO 50 Hz

CMM 1322 0M 1142 0	
Nominal pumping speed	300 m <sup>3</sup> /h
Ultimate pressure	10 hPa(mbar)
Nominal motor rating	9.5 kW
Nominal motor speed	3000 min <sup>-1</sup>
Dimensions (L x W x H)	1385 x 546 x 1184 mm
Gas inlet	G 2"
Gas outlet	G 1¼"

The following technical values refer to ISO 60 Hz

CMM 1322 0M 1142 0	
Nominal pumping speed	360 m <sup>3</sup> /h
Ultimate pressure	10 hPa(mbar)
Nominal motor rating	12.8 kW
Nominal motor speed	3600 min <sup>-1</sup>
Dimensions (L x W x H)	1385 x 546 x 1184 mm
Gas inlet	G 2"
Gas outlet	G 1¼"

## DO YOU WANT TO KNOW MORE

Please contact us!  
info@buschusa.com or +1-800-USA-PUMP



CONTACT FORM



CALL US NOW