

# Genuine Oils VM 032-150

Mineral Oils



VACUUM SOLUTIONS



## Proven performance

Proven mineral oils, for standard industrial applications, for temperatures up to 80 °C

## Cost-effective

Proven wear protection, less maintenance costs

## Reliable

Optimum lubrication properties, perfectly adapted to Busch vacuum pumps, prevent sealing leakage

# Genuine Oils VM 032-150

Mineral Oils



## Dimensional drawing

The following technical values refer to ISO Hz

	VM 032	VM 068	VM 100	VM 150
<b>Base lubricant</b>	Mineral	Mineral	Mineral	Mineral
<b>Viscosity class</b>	ISO VG 32	ISO VG 68	ISO VG 100	ISO VG 150
<b>Kin. viscosity at 40°C</b>	32 mm <sup>2</sup> /s	68 mm <sup>2</sup> /s	100 mm <sup>2</sup> /s	150 mm <sup>2</sup> /s
<b>Kin. viscosity at 100°C</b>	5.2 mm <sup>2</sup> /s	8.5 mm <sup>2</sup> /s	10.7 mm <sup>2</sup> /s	14.5 mm <sup>2</sup> /s
<b>Density at 15° C</b>	0.872 kg/l	0.884 kg/l	0.880 kg/l	0.891 kg/l
<b>Flash point (COC)</b>	225 °C	235 °C	265 °C	275 °C
<b>Pour point</b>	-18 °C	-15 °C	-12 °C	-12 °C

**DO YOU WANT TO KNOW MORE**

Please contact us!  
[info@buschusa.com](mailto:info@buschusa.com) or +1-800-USA-PUMP



CONTACT FORM



CALL US NOW