

# Genuine Oils VSB 032-100

Synthetic Food-Grade Oils



VACUUM SOLUTIONS



## High performance

Synthetic oils based on polyalphaolefin (PAO), outstanding viscosity-temperature stability for optimum lubrication properties even at elevated operating temperatures, excellent cold start characteristics for low temperature applications, outstanding water and air separation for constant effective lubrication

## Efficient

Four times longer durability than comparable mineral oils, outstanding thermal and oxidative stability, extended change intervals, counteract premature wear, reduce energy consumption, high resistance to water ingress

## Food-grade

Ideally suited for all demanding food applications, H1, Halal and Kosher certification, almost odorless and tasteless, no declarable substances according to REACH regulation

# Genuine Oils VSB 032-100

Synthetic Food-Grade Oils



## Dimensional drawing

The following technical values refer to ISO Hz

	VSB 032	VSB 068	VSB 100
<b>Base lubricant</b>	Polyalphaolefin (PAO)	Polyalphaolefin (PAO)	Polyalphaolefin (PAO)
<b>Viscosity class</b>	ISO VG 32	ISO VG 68	ISO VG 100
<b>Kin. viscosity at 40°C</b>	30.5 mm <sup>2</sup> /s	74 mm <sup>2</sup> /s	101 mm <sup>2</sup> /s
<b>Kin. viscosity at 100°C</b>	5.8 mm <sup>2</sup> /s	10.9 mm <sup>2</sup> /s	14.9 mm <sup>2</sup> /s
<b>Viscosity index VI</b>	135	137	154
<b>Total acid number</b>	0.66 mg KOH/g	0.7 mg KOH/g	0.68 mg KOH/g
<b>Density at 15.6° C</b>	0.828 kg/l	0.839 kg/l	0.843 kg/l
<b>Flash point (COC)</b>	234 °C	248 °C	255 °C
<b>Pour point</b>	-66 °C	-39 °C	-42 °C
<b>Food certification - H1</b>	InS	InS	InS
<b>Halal certification</b>	HQC	HQC	HQC
<b>Kosher certification</b>	Rabbinate Aachen	Rabbinate Aachen	Rabbinate Aachen

## DO YOU WANT TO KNOW MORE

Please contact us!  
[info@buschusa.com](mailto:info@buschusa.com) or +1-800-USA-PUMP



CONTACT FORM



CALL US NOW